

## **APPENDIX B**

### **Capacity/Level-of-Service Analysis Methodology**

## CAPACITY/LEVEL-OF-SERVICE ANALYSIS METHODOLOGY

The detailed capacity/level-of-service analysis contained in this traffic impact study was performed in accordance with the standard techniques contained in the "Highway Capacity Manual".<sup>(1)</sup> By definition, capacity represents "the maximum rate of flow that can reasonably be expected to pass a point on a uniform section of a lane or roadway under prevailing roadway, traffic, and control conditions." The level of functioning of an intersection or a uniform section of a lane or roadway can be expressed in terms of levels of service. Level of service (LOS) is defined as "a qualitative measure describing operational conditions within a traffic stream, and their perception by motorists and/or passengers". Such measures include "speed and travel time, freedom to maneuver, traffic interruptions, comfort and convenience, and safety."

At unsignalized intersections, a methodology for evaluating the relative functioning of intersections controlled by stop or yield signs has been developed, and is based on several assumptions, including:

- Major street flows are not affected by the minor (stop-sign controlled) street movements.
- Left turns from the major street to the minor street are influenced only by opposing major street through flow.
- Minor street left turns are impeded by all major street traffic plus opposing minor street traffic.
- Minor street through traffic is impeded by all major street traffic.
- Minor street right turns are impeded only by the major street traffic coming from the left.

The concept of stop-controlled or yield-controlled intersection analysis is based on the estimate of average total delay on minor streets. The methodology of analysis relies on three elements: the size and distribution of gaps in the major traffic stream, the usefulness of these gaps to the minor stream drivers, and the relative priority of the various traffic streams at the intersection. The results of the analysis provide an estimate of average total delay for the various critical movements at the unsignalized intersections. Correlation between average total delay and the respective levels of service are provided for unsignalized intersections as follows:

Level of Service	<i>Unsignalized Intersections</i>	
	Description	Control Delay Per Vehicle (seconds)
A	Little or no delay	≤ 10.0
B	Short traffic delays	10.1 to 15.0
C	Average traffic delays	15.1 to 25.0
D	Long traffic delays	25.1 to 35.0
E	Very long traffic delays	35.1 to 50.0
F	Demand exceeds capacity of the lane or approach	> 50.0

<sup>(1)</sup> *Transportation Research Board, Special Report 209, Highway Capacity Manual, published by the Transportation Research Board, Washington, DC, Updated 2000.*

At signalized intersections, an additional element must be considered: time allocation. Level of service is based primarily on the average control delay per vehicle for various movements within the intersection. Volume/capacity relationships also affect level of service. Thus, both volume/capacity and delay must be considered to evaluate the overall operation of a signalized intersection. Correlation between average delay per vehicle and the respective levels of service are provided for signalized intersections as follows:

<i>Signalized Intersections</i>		
<b>Level of Service</b>	<b>Description</b>	<b>Control Delay Per Vehicle (seconds)</b>
A	Very low delay, high quality flow	≤ 10.0
B	Low delay, good traffic flow	10.1 to 20.0
C	Average delay, stable traffic flow	20.1 to 35.0
D	Longer delay, approach capacity flow	35.1 to 55.0
E	Limit of acceptable delay, capacity flow	55.1 to 80.0
F	Unacceptable delay, forced flow	> 80.0